



Product Type: Plug-in terminal-Socket

Product Name:MC-PA3.5A09-I-0002

Product Description: Pitch: 3.5mm Rated
Voltage : 160V Rated Current: 8A
colour : customizable

Parameters

⌘ SUPU ID	MC-PA3.5A09-I-0002
⌘ Pitch	3.5
⌘ Number of connections	9
⌘ Connection method	-
⌘ Protection Level	IP20
⌘ Operating temperature range	-40~+105°C
⌘ Insulation material	PA66
⌘ Insulation material group	I
⌘ Contact material	Copper alloy
⌘ Contact plating	Sn,Plated
⌘ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

⌘ IEC Rated Current	160V
⌘ IEC Rated Voltage	8A

☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	2.5KV 2.5KV 2.5KV
☞ UL Rated Current	8A - 8A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	M2.5
☞ Stripping length	-
☞ Use group	B/C/D

Commercial data

☞ Order No	MC-PA3.5A09-I-0002
------------	--------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-12 01:53

The right to modify data belongs to SUPU.