





Product Type: Push-in spring terminal

Product Name:TPIO1.5-S-4-PE

Product Description: Connection method:Push in connection,IEC Rated Current:13.5A,IEC Rated Voltage:250V,Number of connections:5,Number of levels : 1,Rated cross section:26-14AWG

Product Size



Parameters

⌘ SUPU ID	TPIO1.5-S-4-PE
⌘ Width	3.5mm
⌘ Number of levels	1
⌘ Number of connections	5

☞ Connection method	直插弹簧接线
☞ Protection Level	IP20
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Ambient temperature (operation)	-40℃~105℃
☞ Ambient temperature (assembly)	-5℃~70℃
☞ Ambient temperature (storage)	-25℃~60℃
☞ Permissible humidity (storage/transport)	30%~70%

Technical data

☞ IEC Rated Current	13.5A
☞ IEC Rated Voltage	250V
☞ Overvoltage category	III
☞ Degree of pollution	3
☞ Rated impulse voltage	4KV
☞ UL Rated Current	15A/15A/10A
☞ UL Rated Voltage	300V
☞ Conductor cross section rigid	0.2-1.5mm ²
☞ Conductor cross section flexible	0.2-1.0mm ²
☞ Conductor cross section flexible,with furrule	0.2-1.0mm ²
☞ Stripping length	8-10mm
☞ Use group	B/C/D

Commercial data

☞ Order No

TPIO1.5-S-4-PE

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat