





Product Type: IP67 connector

Product Name:ESF-RS300A95YL

Product Description: Connectors suitable for energy storage modules Color: Orange Rated voltage: 1500V DC Rated current: 300A Connection method: Nuts Contact type: Pin wire cross-section: 95mm<sup>2</sup> cable outer diameter: 15.2mm to 17.7mm

Product Size



Parameters

☞ SUPU ID	ESF-RS300A95YL
☞ Number of connections	1
☞ Connection method	Bolt connection
☞ Protection Level	IP 67

☞ Operating temperature range	-40°C~+125°C
☞ Insulation material	III
☞ Insulation material group	III
☞ Contact material	Copper alloy
☞ Contact plating	Ag,Plated
☞ Insertion/withdrawal cycles	100
☞ Insertion force	≤75N
☞ Withdrawal force	≥10N

## Technical data

☞ IEC Rated Current	300A
☞ IEC Rated Voltage	1500V DC
☞ Overvoltage category	III
☞ Degree of pollution	3
☞ Rated impulse voltage	12.3KV
☞ Stripping length	20±1mm
☞ Rated cross section(AWG)	3/0 AWG
☞ External cable diameter	15.2mm~17.7mm

## Commercial data

☞ Order No	ESF-RS300A95YL
☞ Packing unit	Pcs
☞ Minimum order quantity	1
☞ Single piece weight	85g

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2026-06-13 13:18

The right to modify data belongs to SUPU.