


Product Type: Plug-in terminal-Plug

Product Name:MC-RQ7.62HXP-0001

Product Description: Pitch:7.62mm Rated Voltage : 1000V Rated Current:41A Connection method : Push in connection colour : customizable

Product Size



Parameters

| | |
|-------------------------|---------------------------|
| ⌘ SUPU ID | MC-RQ7.62HXP-0001 |
| ⌘ Pitch | 7.62 |
| ⌘ Number of connections | XX |
| ⌘ Connection method | Push in spring connection |

| | |
|-------------------------------|----------------------------------|
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PPA |
| ☞ Insulation material group | I |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Sn,Plated |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|---|-----------------------|
| ☞ IEC Rated Current | 41A |
| ☞ IEC Rated Voltage | 1000V |
| ☞ Overvoltage category | III/III/ II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 8.0KV8.0KV8.0KV |
| ☞ UL Rated Current | 35A 35A - |
| ☞ UL Rated Voltage | 600V 600V - |
| ☞ Conductor cross section rigid | 0.2-10mm ² |
| ☞ Conductor cross section flexible | 0.2-6mm ² |
| ☞ Conductor cross section flexible,with furrule | 0.2-6mm ² |
| ☞ Locking screw Specification | - |
| ☞ Locking screw torque | - |
| ☞ Fixed Screw Specification | - |
| ☞ Stripping length | 13-15mm |
| ☞ Use group | B/C/D |

☞ Order No

MC-RQ7.62HXXP-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat