


Product Type: Plug-in terminal-Socket

Product Name:MC-  
PQ7.62H12P-I-0001

Product Description: Pitch:7.62mm Rated Voltage : 1000V Rated Current:41A Connection method : Push-in spring connection colour : customizable

## Product Size



## Parameters

|                         |                      |
|-------------------------|----------------------|
| ⌘ SUPU ID               | MC-PQ7.62H12P-I-0001 |
| ⌘ Pitch                 | 7.62                 |
| ⌘ Number of levels      | Single layer         |
| ⌘ Number of connections | 12                   |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | Push in connection               |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|   |                         |
|---|-------------------------|
| ☞ IEC Rated Current                             | 1000V                   |
| ☞ IEC Rated Voltage                             | 41A                     |
| ☞ Overvoltage category                          | III/III/ II             |
| ☞ Degree of pollution                           | 3 2 2                   |
| ☞ Rated impulse voltage                         | 8.0KV 8.0KV 8.0KV       |
| ☞ UL Rated Current                              | 35A - 35A               |
| ☞ UL Rated Voltage                              | 600V - 600V             |
| ☞ Conductor cross section rigid                 | 0.2~10.0mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2~10.0mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with ferrule | 0.2~6.0mm <sup>2</sup>  |
| ☞ Locking screw Specification                   | -                       |
| ☞ Locking screw torque                          | -                       |
| ☞ Fixed Screw Specification                     | -                       |
| ☞ 固定螺钉扭矩  | -                       |

|                       |         |
|-----------------------|---------|
| ☞ Stripping length    | 13~15mm |
| ☞ Use group           | B/C/D   |
| ☞ Rated cross section | 24~8AWG |

## Commercial data

|            |                      |
|------------|----------------------|
| ☞ Order No | MC-PQ7.62H12P-I-0001 |
|------------|----------------------|

### Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat