



Product Description: Pitch:5.0mm Rated
Voltage : 320V Rated Current:10A
colour : customizable

The technical drawing illustrates the dimensions of the 60mm x 60mm x 28mm connector. It includes three main views:

- Front View (Top Left):** Shows the overall width of 60.00 mm and height of 28.45 mm. The mounting holes are spaced at 3.50 ± 0.30 mm from the bottom edge.
- Side View (Bottom Left):** Shows the profile of the connector with a total width of 60.00 mm and a central slot width of 3.50 mm.
- Top View (Right):** Shows the layout of the mounting holes. The distance between the centerlines of the two rows of holes is 20.00 mm. The distance from the centerline of the holes to the right edge is 3.50 mm. The hole diameter is specified as $\phi 1.40$ (建议孔径尺寸).

⌘ SUPU ID	MC-DPA5.0V30-0002
⌘ Pitch	5
⌘ Number of levels	double-layer
⌘ Number of connections	30

☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	320V
☞ IEC Rated Voltage	10A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	4.0KV 4.0KV 4.0KV
☞ UL Rated Current	15A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ 固定螺钉扭矩	-

☞ Stripping length	-
☞ Use group	B/C/D
☞ Rated cross section	-

Commercial data

☞ Order No	MC-DPA5.0V30-0002
------------	-------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat