



|                               |               |
|-------------------------------|---------------|
| ☞ Connection method           | Cold pressing |
| ☞ Protection Level            | IP20          |
| ☞ Operating temperature range | -40~+105°C    |
| ☞ Insulation material         | PBT           |
| ☞ Insulation material group   | II            |
| ☞ Contact material            | Copper alloy  |
| ☞ Contact plating             | Sn,Plated     |

## Technical data

|   |             |
|---|-------------|
| ☞ IEC Rated Current                             | 8A          |
| ☞ IEC Rated Voltage                             | 320V        |
| ☞ Overvoltage category                          | III/III/ II |
| ☞ Degree of pollution                           | 3 2 2       |
| ☞ Rated impulse voltage                         | 4KV 4KV 4KV |
| ☞ UL Rated Current                              | 8A          |
| ☞ UL Rated Voltage                              | 600V        |
| ☞ Conductor cross section rigid                 | -           |
| ☞ Conductor cross section flexible              | -           |
| ☞ Conductor cross section flexible,with furrule | -           |
| ☞ Locking screw Specification                   | -           |
| ☞ Locking screw torque                          | -           |
| ☞ Fixed Screw Specification                     | -           |
| ☞ 固定螺钉扭矩  | -           |
| ☞ Stripping length                              | -           |

☞ Use group -

☞ Rated cross section -

## Commercial data

☞ Order No

DP508H2XXF-BK-XY10

### Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-04-27 10:55

The right to modify data belongs to SUPU.